

BASIC FEATURES

AGE GROUP: 5 to 12 years old

FALL HEIGHT (CSA): 150" (3,8m) (ASTM): 150" (3,8m)

CHILD CAPACITY: 31 children

SHOCK ABSORBING SURFACE (CSA): 29' x 36' (8,8m x 11m)

SHOCK ABSORBING SURFACE (ASTM): 29' x 36' (8,8m x 11m)



DESCRIPTION

A beautiful mix of flexible cables and rubber straps. This climber offers a coordination and strength development challenge for different muscle groups.

BODY MOVEMENTS



Climbing
Intensive (10)



Balancing
Intensive (10)



Pulling up
Intensive (10)



Hanging
Intensive (10)



Socializing
Moderate (5)

MATERIALS

FLEXIBLE MATERIALS

Cable(s): Cable 5/8" (16 mm) in diameter composed of 6 strands of 8 galvanised steel wires each, wrapped with black polyester, linked together using aluminium joints.

Rubber: 1/4" thick rubber strap made of two rubber layers laminated with two polyester linings. The top has a non-skid texture and the lining is visible on the underside.

METALS

Post(s): 6061-T6 aluminum alloy tube measuring 5" (127mm) in outer diameter, with 0.125" wall thickness.

Hardware: Made of stainless steel, Anti-vandal type.

Hardware: Made of stainless steel, camouflaged by HDPE safety caps.

PLASTIC MATERIALS

Plate(s): Panels are made of HDPE polyethylene colored in the mass and treated against UV rays. All edges are rounded for maximum safety.(iv)

Transparent Material: 1/2" colored translucent resin panel

ANCHORING



IN CONCRETE

This product is anchored to the ground with concrete columns.

COLOUR CHOICES

Aluminum / Steel



Polyethylene Panels (1/2")



Translucent resin panel (1/2")



Made at our factory in Lévis, Québec, Canada • Meets CAN/CSA-Z614 and ASTM ASTM F1487