Climbing walls tower • K-22012

nınıka

BASIC FEATURES

AGE GROUP: **5 to 12 years old** FALL HEIGHT (CSA): **111" (2,8m)** (ASTM): **111" (2,8m)** CHILD CAPACITY: **3 children** SHOCK ABSORBING SURFACE (CSA): **21' x 22' (6,4m x 6,7m)** SHOCK ABSORBING SURFACE (ASTM): **21' x 22' (6,4m x 6,7m)**

DESCRIPTION

A major piece of the Nin-Ka range. Two walls equipped with climbing holds and a very original rung ladder are complemented by numerous handles and steps.

This product is anchored to the ground with concrete

BODY MOVEMENTS

Climbing Intensive (10) Hanging Intensive (10)

ANCHORING

columns.

IN CONCRETE



MATERIALS

METALS Metal frame(s): 6061-T6 aluminum alloy tube measuring 5" (127mm) in outer diameter, with 0.125" wall thickness.

Hardware: Made of stainless steel, Anti-vandal type.

COATINGS

Paint: Painted metal parts are white blasted first, then coated with a primer and Z-series polyester powder, which has an extreme resistance to ultraviolet (UV) rays and weather. Our paint also has antibacterial and antiviral properties (Iv)

PLASTIC MATERIALS

Plate(s) and Panels and other plastic parts are made of HDPE polyethylene panel(s): colored in the mass and treated against UV rays. One side is textured to increase grip. All edges are rounded for maximum safety.

COMPOSITES MATERIALS

Climbing grip(s): Polyester resin made of 10% recycled materials, with a non-slip finish.

COLOUR CHOICES



Made at our factory in Lévis, Québec, Canada • Meets CAN/CSA-Z614 and ASTM ASTM F1487

